



# Powerful & Compact



# **High torque**

36<sub>Nm</sub> Shortest body length 170<sub>mm</sub>

## Runtime per charge\*2

Drilled holes through 18mm thick American pine with ø18 mm auger bit.

#### Approx.





- \*1 : As of August 2014. Among the 10.8V cordless driver drills made by leading power tool manufacturers (surveyed by Hitachi Koki.)
- \*2 : The value is for purpose of reference when 1.5Ah battery BCL 1015 attached. It may vary according to the drilled material and operating conditions.

### Hitachi Cordless Driver Drill 10.87 DS 10DAL

#### **Specifications**

Model		DS 10DAL		
Drill Chuck		0.8 - 10mm (1/32 - 3/8") Keyless		
Capacity	Mild Steel	10mm (3/8")		
	Soft Wood	29mm (1-1/8")		
	Wood Screw	5.8 x 45mm (#12 x 1-25/32")		
	Machine Screw	6mm (1/4")		
Battery Voltage		10.8V		
No Load Speed : High		0 - 1,300/min		
No Load Speed : Low		0 - 350/min		
Max Torque Hard		36Nm (318inlbs.)		
Max Torque Soft		14Nm (124inlbs.)		
Torque Setting		1 - 4.5Nm (9 - 40inlbs.)		
Overall Length		170mm (6-11/16")		
Weight*1		1.0kg (2.2lbs.) with BCL 1015 or BCL 1015S / 1.2kg (2.6lbs.) with BCL 1030		
Standard Accessories		2 Batteries (BCL 1015 or BCL 1015S or BCL 1030), Charger (UC 10SL2), Driver Bit, Battery Cover, Carrying Case		

#### **Charging Time**

	Charger			
Voltage	Model	Capacity*2	UC 10SL2	
	BCL 1015S	1.3Ah	Approx. 25min.	
10.8V	BCL 1015	1.5Ah	Approx. 30min.	
	BCL 1030	3.0Ah	Approx. 60min.	

- \*1. Weight according to EPTA-Procedure 01/2003. \*2. The figures of battery capacity are nominal values.

Distributed by:		

Hitachi Koki Co., Ltd.

www.hitachi-koki.com